

WE REQUIRE PRE-PRODUCTION SAMPLES IN ALL OUR ARTWORKS. IF THE SUPPLIER FAILS TO PRODUCE AN ACCEPTABLE SAMPLE WE MAY REQUEST A FULL REFUND.



 PANTONE 1655 C

Checkbox

This dots must be filled depending the input and output voltage of the product

Qian

- American Model:** Input Voltage: 110 / 120 VAC
Output Voltage: 110 / 115 / 120 VAC
Surge-protected outlets: 4
- Europe Model:** Input Voltage: 220 / 230 VAC
Output Voltage: 220 / 230 VAC
Surge-protected outlets: 2

UPS Capacity: 500VA / 300W
AC Voltage Regulation: ±10% (Bat mode)
Transfer time: Typical 2-6 ms
Waveforms: Simulated Sine Wave (Bat mode)
Recharge Time: 4-6 Hours recover to 90% capacity
Full protection: Overload, discharges, over charge, short circuit, over / under voltage protection

- Modelo Americano:** Voltaje de entrada: 110 / 120 VCA
Voltaje de salida: 110 / 115 / 120 VCA
Enchufes protegidos: 4
- Modelo Europeo:** Voltaje de entrada: 220 / 230 VCA
Voltaje de salida: 220 / 230 VCA
Enchufes protegidos: 2

Capacidad de la PSU: 500VA / 300W
Regulación de Voltaje CA: ±10% (Modo batería)
Tiempo de transferencia: Normalmente 2-6 ms
Forma de onda: Onda Sinusoidal Simulada (Modo batería)
Tiempo de recarga: 4-6 horas para una carga de 90%
Función de protección: sobrecarga, descargas, sobrecarga corta circuito, sobre voltaje, bajo voltaje

7 500619 000659 [SERIAL NUMBER]

Serial number sticker
40 mm
15 mm
CODE-128 BARCODE
PLEASE CONTACT TO PH OR JIMMY ZHU TO KNOW THE CORRECT "SERIAL NUMBER"

California Proposition 65 Warning
Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information visit: www.p65warnings.ca.gov